







Composition -	surface	BCI	Nylon 100%	dyeing method o	f yarn Piece Dyed	
	base fabric	Nonwoven Polyester		backing	PVC and Glass Fiber	
Specification	size	500mm×500mm		overall thickne	ess 6.5mm	
	pile height	3.5mm (loop pile)				
	gauge	1/10	stitch	13.0	yarn weight (oz/sq.yd) 17.7	
JIS Registered No.	No.QT0508001 QT0408001 (JIS L 4406 Carpet Tile)					

Packing	20pcs/box = 5m ² /box				
Net Weight	24.0kg/box				
Performance	Critical Radiant Flux	(ASTM E648) Class 1 Average CRF 0.45/cm² or higher			
	Smoke Density	(ASTM E662) Less than 450			
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0830367			
	Antistatic	Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Stain-resistant	Stain Release / ◆ Stain Release (NANO CLEAN)			
	Formaldehyde Radiation	F [™] ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No.J04-30066			
Way of Installation	Quarter Turn				
Recommended	TOLI ECO GA Cement	(vacuired sugntity) for steel or plastic sub-floor 40 to 60 gram/m ²			
Adhesive from TOLI	TOLI ECO GA Cement EX	(required quantity) for mortar and wood sub-floor 60 to 100 gram/m ²			
Custom Order	All the standard colors of GA-100 can be made with Nano Clean finish (patent-obtained special stain release) on a made-to-order basis. For more information, please contact TOLI sales reps.				
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	Please note that the product has the indigenous odor from its materials.				


MADE IN JAPAN





NANO CLEAN

"Nano Clean" provides more excellent stain resistance to soils by adding special Nano finish to the existing stain release by water-repellent finished.










GA126

|| GA139




























GA1026

GA155















▲ GA190/GA196/GA1021/GA1025/GA1028

